GEDA 300Z DOUBLE BARROW

300kg Double Barrow Electric Hoists



This double barrow rack and pinion hoist can be used for materials only. The "Double Barrow" hoist's cage is twice the size of the regular Geda 300Z's, so is ideal for more bulky loads up to 300kg - Geda 300Z Double Barrow hoists can be attached to scaffold or directly to a building using wall mounts.

GEDA 300Z DOUBLE BARROW GOODS LIFTS

FEATURES

Rack and Pinion

Double Barrow Load Platform

Overload Safety Device

Automatic Landing Control

✓ Interlocked Gate System

KEY SPECIFICATIONS



Up to 50 Metres



Safe Working Load 300kg



230V Single Phase

SPECIFICATIONS

Lift Speed 13 m/min

BASIC WEIGHTS

Without ground enclosure with 50m cable drum

600kg

Total with a constructed height of

Approx. 2500kg

POWER REQUIREMENTS

230V 50Hz Operating Current 9.1 Amps Start Current 38 Amps

BASE UNIT AS STANDARD

BS4343 Industrial Free Straight Plug 16 Amp Single Phase Neutral & Earth (as RS part number 464-1469).

'C' - Rated Breaker 2 metre mains lead

The Geda 300Z Double Barrow hoist can be delivered on its own trailer.

DIMENSIONS

Platform Dimensions

Approx. 1.7m x 1.4m Approx. 5' 7" x 4' 6"


Space Requirements inc. ground enclosure

Approx. 2.8m x 2.95m Approx. 9' 2¹/₄" x 9' 8¹/₄"

Transportation Trailer:Axel Width

2.1m / 6' 10½" Loaded Trailer Height

2.8m / 9' 3"





HIRE | SALES | SERVICE | TRAINING

Call: 01279 501501

Email: info@rapidplatforms.co.uk Visit: www.rapidplatforms.co.uk

Rapid Platforms Ltd, London Road, Spellbrook, Bishop's Stortford, Herts, CM23 4AU

GEDA 300Z DOUBLE BARROW 300kg Double Barrow Electric Hoists GROUND PLAN The hoist can only be erected to land in the configuration shown 50 Λ 0.50 1.42 2.92 **GROUND LEVEL LOADING LOADING AT LIFT LEVEL**



HIRE | SALES | SERVICE | TRAINING

Call: 01279 501501

Email: info@rapidplatforms.co.uk Visit: www.rapidplatforms.co.uk

Rapid Platforms Ltd, London Road, Spellbrook, Bishop's Stortford, Herts, CM23 4AU